

# Glazed ceramic connection blocks. Nickel plated connectors

## Main features

**Ceramic:** Ker 110 (feldspar ceramic SiO<sub>2</sub>-Al<sub>2</sub>O<sub>3</sub>) glazed 5 sides.

- Bulk density : >2.3 g/cm<sup>3</sup>
- Water absorption : max 2% (on unglazed side)
- Flexural strength : 80 Mpa/cm<sup>2</sup>
- Coefficient of thermal expansion : <6 10<sup>-6</sup> mm/°C (20-100°C)
- Volume resistivity : >10<sup>10</sup> ohms.cm at 100°C
- Dielectric strength : 10 Kv/mm
- Terminal numbering: 1, 2, 3, 4

**Screws:** Nickel plated steel (Sae1045). Clamping with or without pressure plate upon types


**Terminals:** Nickel plated brass (63.5~68% Cu)

**Maximum ambient temperature, as per EN60730-1(§14-1) :**

- on ceramic: 425°C (800°F)
- on nickel plated brass connectors: 230°C (445°F)

**Voltage:** 250V to 400V upon types and sizes

**Applicable standards:** (IEC)EN 60998-1 and (IEC) EN60998-2-1 (August 1993)



## Main references



















Picture	Drawing	Ways	Dimensions +/-1mm (mm)	Mounting hole (mm)	Clamping screw*	Connector hole dia. (mm)	Electrical Rating**	Nominal gauge (mm <sup>2</sup> )	Wires gauge, rigid or flexible (mm <sup>2</sup> )	Weight	References***
		1	11x19x15.5	0	M3	3	32	4	1.5; 2.5; 4	7	BV1V1
		2	22x19x15.5	1 x 4.1	M3	3	32	4	1.5; 2.5; 4	13	BV2V2
		3	35x19x15.5	2 x 4.1, distance 11mm	M3	3	32	4	1.5; 2.5; 4	20	BV3V3
		4	45x19x15.5	3 x 4.1, distance 11mm	M3	3	32	4	1.5; 2.5; 4	26	BV4V4
		1	12x20x17	0	M3	3.5	41	6	2.5; 4 (6mm <sup>2</sup> rigid only)	9	BN1N1
		2	23x20x17	1 x 4.1	M3	3.5	41	6	2.5; 4 (6mm <sup>2</sup> rigid only)	15	BN2N2
		3	35x20x17	2 x 4.1, distance 12mm	M3	3.5	41	6	2.5; 4 (6mm <sup>2</sup> rigid only)	25	BN3N3

Because of permanent improvement of our products, drawings, descriptions, features used on these data sheets are for guidance only and can be modified without prior advice



# Glazed ceramic connection blocks. Nickel plated connectors

Because of permanent improvement of our products, drawings, descriptions, features used on these data sheets are for guidance only and can be modified without prior advice

		4	47x20x17	3 x 4.1, distance 12 mm	M3	3.5	41	6	2.5; 4 (6mm <sup>2</sup> rigid only)	33	BN4N4
		1	12x23x20	0	M3.5	4.3	57	10	4 ; 6; (10 mm <sup>2</sup> rigid only)	13	BP1P1
		2	25x23x20	1 x 4.5	M3.5	4.3	57	10	4 ; 6; (10 mm <sup>2</sup> rigid only)	26	BP2P2
		3	39x23x20	2 x 4.5 distance 13 mm	M3.5	4.3	57	10	4 ; 6; (10 mm <sup>2</sup> rigid only)	42	BP3P3
		4	52x23x20	3 x 4.5 distance 13 mm	M3.5	4.3	57	10	4 ; 6; (10 mm <sup>2</sup> rigid only)	51	BP4P4
		1	16x31x23	0	M4	5.5	76	16	6 ; 10, (16 mm <sup>2</sup> rigid only)	27	BQ1Q1
		2	35x31x23	1 x 5.5	M4	5.5	76	16	6 ; 10 ; 16	58	BQ2Q2
		3	51x31x23	2 x 5.5 distance 18 mm	M4	5.5	76	16	6 ; 10 ; 16	81	BQ3Q3
		4	69x31x23	3x5.5 distance 18 mm	M4	5.5	76	16	6 ; 10 ; 16	103	BQ4Q4

\* Recommended clamping torque M3: 0.6 Nm, M3.5: 0.8Nm, M4 : 1.2Nm

\*\* Test current upon IEC60998-1.

\*\*\* These ceramic blocs also exist with stainless steel pressure plate, Add « P » behind the reference

