





Very high temperature steatite connection blocks, 750V range



Not protected against accidental electric contact, nickel terminals, stainless steel screws, nickel pressure plate



35mm²

Mounting on 35mm Din rail is possible

BK351 136 gr. 	SOLID CABLE 11-17 mm 35mm ² / 25mm ² / 16mm ² AWG2 / AWG4 / AWG6	BK352 242 gr.
BK353 353 gr. 	2.5 N.m 750V Permanent: 500°C/930°F Peak: 700°C/1290°F 950°C/1740°F*	BK354 470 gr.

50mm²**

Mounting on 35mm Din rail is possible

BK501 165 gr. 	SOLID CABLE 12-17.5 mm 50mm ² / 35mm ² / 25mm ² AWG0 / AWG2 / AWG4	BK502 317 gr.
BK503 470 gr. 	3.5 N.m 750V Permanent: 500°C/930°F Peak: 700°C/1290°F 950°C/1740°F*	BK504 630gr.

* : Fire conditions, product must be replaced after it.

** : These cross-section and rating do not exist in EN60998 which is limited to 35mm², so these values are taken from EN60947.

Excerpt from catalogue 10-2

Page (.pdf)	Drawing 2D (.dwg)	Drawing 3D (.stp)		35mm Din rail mounting clip	Reference 66AT410650
-------------	-------------------	-------------------	--	-----------------------------	-------------------------

