

Pigtail bulb room thermostats

Enclosure	Type	Operation	Contact	Measurement	Ranges °C	Models
IP44	Control	Mechanical	SPDT	Ambient		Y035, Y036
Material						
PC-ABS						

Y035: Internal adjustment		Y036: External adjustment	

Housing: IP44, black PC-ABS, fiber glass reinforced, UL94V0. High impact and UV resistance. 2 removable wall mounting lugs.

Cable input: One M20 cable gland.

Set point adjustment: By °C printed knob for external adjustment models, by screw driver and printed dial on internal adjustment models. °F values available as an option.

Sensing element: Liquid filled bulb, coiled on the side of enclosure.

Adjustment range: 4-40°C (40-105°F)

Electrical connections: 3 screw terminal connection block

Mounting: Wall mounting, by two side lugs with holes for dia. 4mm screws, 63mm distance.

Contact: SPDT

Electrical rating, resistive loads:

- Open on temperature rise contact (C-1)
16A 250V, 50 ~60Hz: >100,000 cycles,
20A 250V, 50 ~60Hz: ≥50,000 cycles,
10A 400V, 50 ~60Hz: ≥50,000 cycles.
- Close on temperature rise contact (C-2)

(C-2): 6A 250V 50 ~60Hz: >100,000 cycles

Electrical rating, inductive loads:

- Open on temperature rise contact (C-1): 6A 250V, 50 ~60Hz: >100,000 cycles
- Close on temperature rise contact (C-2): 0.6A 250V 50 ~60Hz: >100,000 cycles.

Minimum storage temperature: -35°C (-30°F)

Maximum ambient temperature: 60°C (140°F)

For more technical information ask 8G thermostat technical data sheet.

References

Temperature ranges °C (°F)	Internal adjustment	External adjustment	Differential °C (°F)	Max temperature on bulb °C (°F)
4-40 (40-105)	Y035GB004040QB3J	Y036GB004040QB3J	1±0.5°C (1.8±1°F)	60 (140)

°F printing: replace last character (J) by K

Knob printings

°C/°F Printing	
4-40°C	40-105°F



Contact us

Web: www.ultimheat.com

Cat2-2-4-7